

HEPT15-TLI

ELECTRIC PALLET TRUCK



HIGHLIGHTS

- Increased stability, compact design
- Long-lasting battery, fast-charge option
- Quiet, eco-friendly operation
- Precise control in tight spaces

BATTERY
LI-ION

MAX LIFT
120MM

RATED LOAD
1500KG

HEPT15-TLI

ELECTRIC PALLET TRUCK



CHARACTERISTICS			
1.1	Drive		Electric
1.2	Operator		Walkie
1.3	Load capacity/rated load	kg	1500
1.4	Load center	mm	600
1.5	Height, fork lowered	mm	80±2
1.6	Wheelbase	mm	1163/1213
1.7	Wheel		PU
1.8	Wheel size, front	mm	190*70
1.9	Wheel size, rear	mm	79*62 (Tandem)
1.10	Wheels, number front/rear (x=drive wheels)		1x+2/4
1.11	Lift	mm	100
1.12	Height of tiller in drive position (min./max.)	mm	590/1265
1.13	Overall length	mm	1615/1665
1.14	Fork length	mm	1150/1200
1.15	Overall width	mm	560/685
1.16	Fork dimensions (h*w*l)	mm	55/155/1150(1200)
1.17	Distance between fork-arms (inside/outside)	mm	250/560 (375/685)
1.18	Ground clearance	mm	30
1.19	Aisle width for pallets 1000×1200 crossways	mm	2153/2180
1.20	Aisle width for pallets 800×1200 lengthways	mm	2068/2089
1.21	Min. turning radius	mm	1374/1425
PERFORMANCE			
2.1	Travel speed, laden/unladen	km/h	4.5/4.5
2.2	Lifting speed, laden/unladen	mm/s	18/23
2.3	Lowering speed, laden/unladen	mm/s	50/40
2.4	Max. gradeability, laden/unladen	%	10%/20%
2.5	Drive motor/Lifting motor	kW	BLDC0.8/DC0.5
BATTERY			
3.1	Battery voltage/nominal capacity	V/Ah	48V/10Ah (48V/15Ah) - (48V/20Ah) (Optional)
3.2	Brake		Electromagnetic / Regenerative
3.3	Sound level at the driver's ear according to EN 12053	dB	<70dB
3.4	Battery weight	kg	6/7.2/8.5
3.5	Service weight including battery	kg	140/142/143
3.6	Charger specification	V/A	48/5 48/10 (Optional)

HEPT15-TLI

ELECTRIC PALLET TRUCK

HEZLIFT

Siamo un rivenditore leader di attrezzature industriali, fornendo prodotti e soluzioni di alta qualità alle aziende in tutto il paese.

Distribuito da Resiltek S.R.L



EMAIL

SALES@HEZLIFT-EUROPE.COM



PHONE

+39 351 7557765



WEBSITE

HEZLIFT-EUROPE.COM

